

## Community Wildfire Hazard Severity / Risk Assessment

Community Name: Country Club Vistas 2 Date: 5/10/2022

Elements	Points	Community Averages
<b>A. Community Design</b>		
1. Ingress and egress		
Two or more, primary roads	1	1
One road, primary route	3	
One way in/out	5	
2. Primary road width		
Minimum of 20 feet	1	1
Less than 20 feet	3	
3. Road Accessibility		
Smooth road, grade of 5% or less	1	1
Rough road, grade of more than 5%	3	
Other	5	
4. Secondary road terminus (if applicable)		
Loop roads, cul-de-sacs		
Outside turning radius is greater than 50 feet	1	1
Outside turning radius is 50 feet or less	3	
Dead-end roads		
Dead-end roads 200 feet or less in length	3	3
Dead-end roads more than 200 feet in length	5	
5. Average lot size		
More than 10 acres	1	
Between 1-10 acres	3	
Less than one acre	5	5
6. Street signs		
Present (4 inches or greater in size and reflectorized)	1	1
Present (4 inches or less in size or not reflectorized)	3	
Not present	5	
<b>B. Vegetation (Fuel Models)</b>		
1. National Fire Danger Rating System fuel models		
Light (grasses, forbs, and sawgrasses)	1	
Medium (light brush and small trees)	5	5
Heavy (dense brush, timber and hardwoods)	10	
Slash (timber harvesting residue)	10	
2. Defensible space		
100 feet of defensible-space treatment around buildings	1	

30-70 feet of defensible-space treatment around buildings	5	5
No defensible-space treatment around building	10	
<b>C. Topography</b>		
1. Slope		
Less than 9%	1	1
Between 10-20%	4	
Between 21-30%	7	
Between 31-40%	8	
Greater than 41%	10	

Page 1 subtotal 24

Elements	Points	Community Averages
<b>D. Additional Rating Factors</b>		
1. Rough topography that contains steep canyons	2	0
2. Areas with a history of higher fire occurrence than surrounding areas due to special situations such as heavy lightning, railroads, escaped debris burning, arson, etc.	3	0
3. Areas that are periodically exposed to unusually severe fire weather and strong dry winds.	4	4
<b>E. Roofing Material</b>		
1. Construction material (See explanation of Uniform Building Code fire-resistance classes)		
<u>Class A roof:</u> (ex. concrete shingles and tile, slate shingles, clay tiles, mineral or fiberglass reinforced asphalt shingles; metal roof or fiber-cement shingles with gypsum underlayment)	1	1
<u>Class B roof:</u> (ex. metal sheets or metal shingles without a gypsum underlayment)	3	
<u>Class C roof:</u> (ex. asphalt shingles and wood shingles chemically treated to resist fire)	5	
<u>Non-rated:</u> (ex. untreated wood shakes and shingles)	10	
Any roof with plastic skylights	10	
<b>F. Existing Building Construction</b>		
1. Materials (predominant)		
Noncombustible siding/deck	1	1
Noncombustible siding/wood deck	5	
Combustible siding and deck	10	
<b>G. Available Fire Protection</b>		
1. Water source availability (on site)		
500 gallons per minute hydrants less than 1000 feet apart	1	

Hydrants producing less or other on-site water source available	2	2
No hydrants or other on-site water resource available	10	
2. Water source availability (off site)		
Sources within 20 minute round-trip	1	
Sources within 21-45 minute round-trip	5	3
Sources greater than a 46 minute round-trip	10	
<b>H. Utilities (Gas and Electric)</b>		
1. Placement		
All underground utilities	1	1
One underground, one aboveground	5	
All aboveground	10	
<b>I. Total for Home (Total all checklist points)</b>		
1. Low Hazard: Less than 49 points		36
2. Moderate Hazard: 49-68 points		
3. High Hazard: 69-83 points		
4. Extreme Hazard: 84+ points		

Site visit completed by:

Matt Rust